



ENVIRONMENTAL LIFE TEST SERVICES

Spirit Electronics' environmental life testing identifies reliability issues early in your product development. Our contract testing laboratory works directly with you to provide testing solutions that help ensure product quality and reliability. As part of your turn-key product solution, reliability study, or on an as-needed basis for overflow/bandwidth, Spirit Electronics can solve your issues before they become a problem in the field. For additional information you can visit our website, or you can call or send us an email to discuss your environmental life testing needs.

HAST

- Unsaturated or saturated humidity control
- Multi-mode system (wet bulb/dry bulb) controls humidity at steady state and during ramps
- Programmable controller with temperature, humidity, and count-down display
- 12 Specimen power terminals, allows power-up of specimens
- Two feed-through ports
- Meets specification EIA/JEDEC Test Method A110 & 102C

THERMAL/HUMIDITY CYCLING & STEADY-STATE

- Temperature range: -70°C to 180°C
- Temperature stability: ± 0.3 °C (up to 100°C)
- Heating rate: 5.2 °C/min
- Cooling rate: 3.5 °C/min
- Humidity range: 10% to 98% RH
- Humidity stability: ± 2.5 % RH
- Feed-through port
- Meets specifications JESD22-A100C, JESD22-A101C, IPC/JEDEC J-STD-020D.1

THERMAL SHOCK

- High temperature exposure: 60°C to 200°C
- Low temperature exposure: -65°C to 0°C
- Temperature stability: ± 0.5 °C
- Feed-through port
- Meets specifications Mil-Std 883 1010.7/1010.8, IEC 61300-2-47, JEDEC JESD47E, JESD22-A104

SUPER UV TESTING

- Up to 30x irradiance over conventional weatherometers
- Acceleration factors up to 110x (material dependent)
- Irradiance: 1500W/m² @ 300-400nm
- Light wavelength: 295-450nm
- Light uniformity: 90%
- Temperature control: 50°C to 85°C during irradiation; 35°C to 75°C during dark; 30°C during dew
- Humidity control: 40% to 70% RH during irradiation; 50% to 90% RH during dark; 97% to 100% RH during dew
- Black panel temperature stability: ± 3 °C



ISO9001: 2015
AS9100: 2016

SPIRIT ELECTRONICS



TAPO/DMEA/DCSA Trusted Supplier
CAGE: 08MH7 | UEI: WJFVKFC33X99